

SE SERIES[®]

SPECIFICATIONS



SE15-25T SPECIFICATIONS

SPECIFICATIONS	1.2	Manufacturer's Designation	SE15T		SE15T		SE15T		SE15T	
	1.3	Wheelbase Category	ESWB		SWB		ESWB-T*		SWB-T*	
	1.4	Battery AH (max)	AH/6hr		660 / 340		880 / 660		775 / 420	
	1.5	Battery Size (WxLxH)	38.8 (986) x 13.8 (350) x 12.8 (625)		38.3 (973) x 19.9 (505) x 22.8 (579)		38.8 (986) x 13.8 (350) x 30.5 (775)		38.3 (973) x 20.0 (508) x 30.5 (775)	
WT	1.6	Actual Battery Compartment Dim (No Gap)	in (mm)		39.2 (996) x 15.7 (400) x 25.8 (655)		39.2 (996) x 21.5 (545) x 25.8 (655)		39.2 (996) x 14.4 (367) x 30.9 (786)	
	1.7	Coupling Height	in (mm)		Elec-36V		Elec-36V/48V		Elec-36V	
	1.8	Operator Type Stand On / Driver Seated			Rider-Seated		Rider-Seated		Rider-Seated	
	1.9	Load Capacity / Rated Load	lbs (Kg)		3000 (1360)		3000 (1360)		3000 (1360)	
TRES, CHASSIS	1.6	Load Center Distance	in (mm)		24 (610)		24 (610)		24 (610)	
	1.8	Load Center Distance, Center of Drive Axle to Fork Face	in (mm)		14.49 (368)		14.41 (366)		14.49 (368)	
	1.9	Wheelbase	in (mm)		46.77 (1188)		52.4 (1331)		46.77 (1188)	
	2.1	Service Weight	lbs (Kg)		7819.9 (3547)		7374.45 (3345)		7894.74 (3581)	
DIMENSIONS	2.2	Axle Loading, Laden Front / Rear	lbs (Kg)		9199.9 (4173) / 1620.4 (735)		8972.8 (4070) / 1404.34 (637)		9250.59 (4196) / 1644.65 (746)	
	2.5	Axle Loading, Unladen Front / Rear	lbs (Kg)		3997 (1813) / 3822.8 (1734)		3769.9 (1710) / 3604.55 (1635)		4047.68 (1836) / 3847.06 (1745)	
	3.1	Tire Type: P = Pneumatic, SE = Superelastic, C = Cushion			SE		SE		SE	
	3.2	Tire Size, Front			18 x 7-8		18 x 7-8		18 x 7-8	
PERFORMANCE	3.3	Tire Size, Rear			140/55-9		140/55-9		140/55-9	
	3.4	Wheels, Number Front / Rear (x= Drive Wheels)			2X/2		2X/2		2X/2	
	3.5	Tread, Front	in (mm)		35.8 (908)		35.8 (908)		35.8 (908)	
	3.6	Tread, Rear	in (mm)		7.44 (189)		7.44 (189)		7.44 (189)	
MISC	4.1	Tilt of Upright/Fork Carriage a/B	deg		5 / 6		5 / 6		5 / 6	
	4.2	Height, upright/lowered	in (mm)		82.87 (2105)		82.87 (2105)		82.87 (2105)	
	4.3	Freelift (w/ LBR)	in (mm)		4.33 (110)		4.33 (110)		4.33 (110)	
	4.7	Height Over Head Guard Std	in (mm)		81.69 (2075)		81.69 (2075)		86.85 (2206)	
WT	4.8	Height Floor to Battery Bottom Std	in (mm)		5.39 (137)		5.39 (137)		5.39 (137)	
	4.9	Seat Height, (Floor to Front Corner)	in (mm)		38.90 (988)		38.90 (988)		44.09 (1120)	
	5.0	Step Height (Floor to Top of Step)	in (mm)		12.64 (321)		12.64 (321)		17.83 (453)	
	5.1	Floorboard Height (Floor to Center of Floorboard)	in (mm)		22.99 (584)		22.99 (584)		28.11 (714)	
DIMENSIONS	5.2	Hood Height (Floor to Top of Hood)	in (mm)		33.27 (845)		33.27 (845)		38.46 (977)	
	5.3	Length to Face of Forks	in (mm)		68.43 (1738)		74.37 (1889)		68.15 (1731)	
	5.4	Width (OAW-Across Drive Tires)	in (mm)		41.73 (1060)		41.97 (1066)		41.73 (1060)	
	5.5	Width (OAW-Across Drive Fenders)	in (mm)		41.50 (1054)		41.50 (1054)		41.50 (1054)	
PERFORMANCE	5.6	Width (Across Frame)	in (mm)		41.50 (1054)		41.50 (1054)		41.50 (1054)	
	5.7	Fork Dimensions	in (mm)		1.5 (38) x 4.0 (102) x 42.0 (1067)		1.5 (38) x 4.0 (102) x 42.0 (1067)		1.5 (38) x 4.0 (102) x 42.0 (1067)	
	5.8	Fork Carriage Width	in (mm)		37.0 (940)		37.0 (940)		37.0 (940)	
	5.9	Ground Clearance Minimum Unladen (Upright)	in (mm)		2.0 (51)		2.0 (51)		2.0 (51)	
MISC	6.0	Ground Clearance Center of Wheelbase	in (mm)		4.09 (104)		4.09 (104)		4.09 (104)	
	6.1	Right Angle Stack (42x48) + 8in clear	in (mm)		128.31 (3259)		133.70 (3396)		127.83 (3247)	
	6.2	Asile Width for Pallets 1000 x 1000 Crossways (42x42) +8in clear	in (mm)		122.64 (3115)		128.03 (3252)		122.17 (3103)	
	6.3	Asile Width for Pallets 800 x 1200 Crossways (32x48) +200mm (8in) clear	in (mm)		114.72 (2914)		132.28 (3360)		114.25 (2902)	
PERFORMANCE	6.4	Turning Radius	in (mm)		54.41 (1382)		59.88 (1521)		53.94 (1370)	
	6.5	Travel Speed Laden / Unladen	mph (Kph)		10.0 (16.1) / 10.0 (16.1)		10.0 (16.1) / 10.0 (16.1)		10.0 (16.1) / 10.0 (16.1)	
	6.6	Lift Speed Laden / Unladen (48V)	fps (mps)		1.54 (0.47) / 2.07 (0.63)		1.54 (0.47) / 2.07 (0.63)		1.54 (0.47) / 2.07 (0.63)	
	6.7	Lowering Speed Laden / Unladen (48V)	fps (mps)		2.03 (0.62) / 1.90 (0.58)		2.03 (0.62) / 1.90 (0.58)		2.03 (0.62) / 1.90 (0.58)	
MISC	6.8	Lift Speed Laden / Unladen (36V)	fps (mps)		1.31 (0.40) / 1.94 (0.59)		1.31 (0.40) / 1.94 (0.59)		1.31 (0.40) / 1.94 (0.59)	
	6.9	Lowering Speed Laden / Unladen (36V)	fps (mps)		2.03 (0.62) / 1.90 (0.58)		2.03 (0.62) / 1.90 (0.58)		2.03 (0.62) / 1.90 (0.58)	
	7.0	Max. Drawbar Pull Laden / Unladen	lbf (N)		3795 (16851) / 2308.11 (10267)		3815.01 (16970) / 2161.31 (9614)		3812.09 (16967) / 2336.89 (10396)	
	7.1	Grade Clearance	%		34.3 / 27.8		36.3 / 27.8		34.2 / 27.9	
WT	7.2	Max. Gradeability Laden / Unladen	%		34.3 / 27.8		36.3 / 27.8		34.2 / 27.9	
	7.3	Service Brake			Electric		Electric		Electric	
	7.4	Battery Weight (Min / Max) 1	lbs (Kg)		1474.89 (669) / 1673.31 (759)		1549.85 (703) / 2334.69 (1059)		1649.06 (748) / 1944.47 (882)	
	7.5	Diameter of Drive Motor	in (mm)		7.87 (200)		7.87 (200)		7.87 (200)	
DIMENSIONS	7.6	Diameter of Hydraulic Motor	in (mm)		7.87 (200)		7.87 (200)		7.87 (200)	
	7.7	Drive, Steer, Hydraulic Motor Control			AC / Inverter		AC / Inverter		AC / Inverter	
	7.8	Sound Level, Driver Ear According to DIN 12053	dB(A)		67		67		67	
	7.9	Towing Coupling, Class / Type DIN			Pin		Pin		Pin	

SE15-25T SPECIFICATIONS

SPECIFICATIONS	1.2	Manufacturer's Designation		SE17T	SE17T	SE20T	SE20T
	1.3	Wheelbase Category		SWB	MWB	MWB	SWB-1*
	1.4	Battery AH (max)	AH/6hr	800 / 600	1100 / 770	1100 / 770	1120 / 750
	1.5	Battery Size (WxLxH)		38.3 (973) x 19.9 (505) x 22.8 (579)	38.3 (973) x 24.4 (620) x 22.8 (579)	38.3 (973) x 24.4 (620) x 22.8 (579)	38.3 (973) x 20.0 (508) x 30.5 (775)
WT	1.6	Actual Battery Compartment Dim (No Gap)	in (mm)	39.2 (996) x 21.5 (545) x 25.8 (655)	39.2 (996) x 25.4 (645) x 25.8 (655)	39.2 (996) x 25.4 (645) x 25.8 (655)	39.2 (996) x 21.5 (545) x 30.9 (786)
	1.7	Coupling Height		Elec-36V/48V	Elec-36V/48V	Elec-36V/48V	Elec-36V
	1.8	Operator Type Stand On / Driver Seated		Rider-Seated	Rider-Seated	Rider-Seated	Rider-Seated
	1.9	Load Capacity / Rated Load	lbs (Kg)	3500 (1588)	3500 (1588)	4000 (1814)	4000 (1814)
TIMES, CHASSIS	1.6	Load Center Distance	in (mm)	24 (610)	24 (610)	24 (610)	24 (610)
	1.8	Load Center Distance, Center of Drive Axle to Fork Face	in (mm)	14.49 (368)	14.49 (368)	14.41 (366)	14.49 (368)
	1.9	Wheelbase	in (mm)	52.4 (1331)	56.3 (1430)	56.3 (1430)	52.4 (1331)
	2.1	Service Weight	lbs (Kg)	7733.81 (3508)	8132.84 (3689)	8038.05 (3646)	8941.94 (4056)
DIMENSIONS	2.2	Axle Loading, Laden Front / Rear	lbs (Kg)	9854.65 (4470) / 1380.09 (626)	10322.03 (4682) / 1309.54 (594)	10796.23 (4898) / 1239.56 (562)	11417.73 (5179) / 1523.4 (691)
	2.3	Axle Loading, Unladen Front / Rear	lbs (Kg)	3787.54 (1718) / 3948.47 (1791)	4252.71 (1929) / 3880.13 (1760)	3862.5 (1752) / 4173.35 (1893)	4482 (2037) / 4527.74 (2022)
	3.1	Tire Type: P = Pneumatic, SE = Superelastic, C = Cushion		SE	SE	SE	SE
	3.2	Tire Size, Front		200/50-10	200/50-10	200/50-10	200/50-10
PERFORMANCE	3.3	Tire Size, Rear		140/55-9	140/55-9	140/55-9	140/55-9
	3.4	Wheels, Number Front / Rear (x= Drive Wheels)		2X2	2X2	2X2	2X2
	3.5	Tread, Front	in (mm)	36.18 (919)	36.18 (919)	36.18 (919)	36.18 (919)
	3.6	Tread, Rear	in (mm)	7.44 (189)	7.44 (189)	7.44 (189)	7.44 (189)
MISC	4.1	Tilt of Upright/Fork Carriage a/B	deg	5 / 6	5 / 6	5 / 6	5 / 6
	4.2	Height, upright/lowered	in (mm)	82.87 (2105)	82.87 (2105)	82.87 (2105)	82.87 (2105)
	4.3	Freelift (w/ LBR)	in (mm)	4.33 (110)	4.33 (110)	4.33 (110)	4.33 (110)
	4.7	Height Over Head Guard Std	in (mm)	81.69 (2075)	81.69 (2075)	81.69 (2075)	86.85 (2206)
WT	4.8	Height Floor to Battery Bottom Std	in (mm)	5.39 (137)	5.39 (137)	5.39 (137)	5.39 (137)
	4.9	Seat Height, (Floor to Front Corner)	in (mm)	38.90 (988)	38.90 (988)	38.90 (988)	44.09 (1120)
	5.0	Step Height (Floor to Top of Step)	in (mm)	12.64 (321)	12.64 (321)	12.64 (321)	17.83 (453)
	5.1	Floorboard Height (Floor to Center of Floorboard)	in (mm)	22.99 (584)	22.99 (584)	22.99 (584)	28.11 (714)
DIMENSIONS	5.2	Hood Height (Floor to Top of Hood)	in (mm)	33.27 (845)	33.27 (845)	33.27 (845)	38.46 (977)
	5.3	Length to Face of Forks	in (mm)	74.37 (1889)	78.31 (1989)	78.31 (1889)	73.74 (1873)
	5.4	Width (OAW-Across Drive Tires)	in (mm)	44.25 (1124)	44.25 (1124)	44.25 (1124)	44.25 (1124)
	5.5	Width (OAW-Across Drive Fenders)	in (mm)	41.50 (1054)	41.50 (1054)	41.50 (1054)	41.50 (1054)
PERFORMANCE	5.6	Width (Across Frame)	in (mm)	41.50 (1054)	41.50 (1054)	41.50 (1054)	41.50 (1054)
	5.7	Fork Dimensions	in (mm)	1.5 (38) x 4.0 (102) x 42.0 (1067)	1.5 (38) x 4.0 (102) x 42.0 (1067)	1.5 (38) x 4.0 (102) x 42.0 (1067)	1.5 (38) x 4.0 (102) x 42.0 (1067)
	5.8	Fork Carriage Width	in (mm)	37.0 (940)	37.0 (940)	37.0 (940)	37.0 (940)
	5.9	Ground Clearance Minimum Unladen (Upright)	in (mm)	2.0 (51)	2.0 (51)	2.0 (51)	2.0 (51)
MISC	6.0	Ground Clearance Center of Wheelbase	in (mm)	4.09 (104)	4.09 (104)	4.09 (104)	4.09 (104)
	6.1	Right Angle Stack (42x48) + 8in clear	in (mm)	133.70 (3396)	137.64 (3496)	137.60 (3495)	133.31 (3386)
	6.2	Asile Width for Pallets 1000 x 1000 Crossways (42x42) +8in clear	in (mm)	128.03 (3252)	131.97 (3352)	131.93 (3495)	127.64 (3242)
	6.3	Asile Width for Pallets 800 x 1200 Crossways (32x48) +200mm (8in) clear	in (mm)	132.28 (3360)	124.06 (3151)	136.18 (3459)	131.89 (3350)
PERFORMANCE	6.4	Turning Radius	in (mm)	59.88 (1521)	63.74 (1619)	63.74 (1619)	59.41 (1509)
	6.5	Travel Speed Laden / Unladen	mph (Kph)	10.0 (16.1) / 10.0 (16.1)	10.0 (16.1) / 10.0 (16.1)	10.0 (16.1) / 10.0 (16.1)	10.0 (16.1) / 10.0 (16.1)
	6.6	Lift Speed Laden / Unladen (48V)	fps (mps)	1.48 (0.45) / 2.07 (0.63)	1.48 (0.45) / 2.07 (0.63)	1.41 (0.43) / 2.07 (0.63)	1.41 (0.43) / 2.07 (0.63)
	6.7	Lowering Speed Laden / Unladen (48V)	fps (mps)	2.03 (0.62) / 1.90 (0.58)	2.03 (0.62) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)
MISC	6.8	Lift Speed Laden / Unladen (36V)	fps (mps)	1.21 (0.37) / 1.94 (0.59)	1.21 (0.37) / 1.94 (0.59)	1.15 (0.35) / 1.94 (0.59)	1.15 (0.35) / 1.94 (0.59)
	6.9	Lowering Speed Laden / Unladen (36V)	fps (mps)	2.03 (0.62) / 1.90 (0.58)	2.03 (0.62) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)
	7.0	Max Drawbar Pull Laden / Unladen	lbf (N)	3811.86 (16956) / 2190.99 (9746)	3812.09 (16957) / 2449.97 (10898)	3812.98 (16961) / 2432.88 (10822)	3817.93 (16983) / 2590.02 (11521)
	7.1	Grade Clearance	%	33.0	31.2	31.2	33.8
WT	7.2	Max Gradeability Laden / Unladen	%	33.0 / 26.5	31.7 / 28.5	28.9 / 26.5	28.1 / 27.3
	7.3	Service Brake		Electric	Electric	Electric	Electric
	7.4	Battery Weight (Min / Max) 1	lbs (Kg)	1549.85 (703) / 2334.69 (1059)	2050.30 (930) / 2861.60 (1298)	2050.30 (930) / 2861.60 (1298)	2590.43 (1175) / 2899.08 (1315)
	7.5	Diameter of Drive Motor	in (mm)	7.87 (200)	7.87 (200)	7.87 (200)	7.87 (200)
DIMENSIONS	7.6	Diameter of Hydraulic Motor	in (mm)	7.87 (200)	7.87 (200)	7.87 (200)	7.87 (200)
	7.7	Drive, Steer, Hydraulic Motor Control		AC / Inverter	AC / Inverter	AC / Inverter	AC / Inverter
	7.8	Sound Level, Driver Ear According to DIN 12053	dB(A)	67	67	67	67
	7.9	Towing Coupling, Class / Type DIN		Pin	Pin	Pin	Pin

SE15-25T SPECIFICATIONS

SPECIFICATIONS	1.2	Manufacturer's Designation		SE20T	SE25T	SE25T
	1.3	Wheelbase Category	MWB-T*	SWB-T*	MWB-T*	
	1.4	Battery AH (max)	4Ah/6h	1250 / 875	1120 / 750	1250 / 875
WT	1.5	Battery Size (Volts/Wh)		38.8 (986) x 25 (635) x 30.5 (775)	38.3 (973) x 20 (508) x 30.5 (775)	38.8 (986) x 25 (635) x 30.5 (775)
	1.6	Actual Battery Compartment Dim (No Gap)	(in mm)	39.2 (996) x 25.4 (645) x 30.9 (786)	39.2 (996) x 21.5 (545) x 30.9 (786)	39.2 (996) x 25.4 (645) x 30.9 (786)
	1.7	Coupling Height		Elec-36V	Elec-36V/48V	Elec-36V
	1.8	Operator Type- Stand On/ Driver Seated		Rider-Seated	Rider-Seated	Rider-Seated
	1.9	Load Capacity / Rated Load	lbs (kg)	4000 (1814)	5000 (2268)	5000 (2268)
	1.10	Load Center Distance	(in mm)	24 (610)	24 (610)	24 (610)
	1.11	Load Load Center Distance, Center of Drive Axle to Fork Face	(in mm)	14.49 (368)	14.41 (366)	14.49 (368)
	1.12	Wheelbase	(in mm)	56.3 (1430)	52.4 (1331)	56.3 (1430)
	1.13	Service Weight	lbs (kg)	8682.4 (4029)	9098.12 (4099)	8637.01 (4462)
	1.14	Weight (Excluding Load) Front / Rear	lbs (kg)	11430.06 (5184)	12903.64 (5854)	11734.56 (5317)
1.15	Weight (Excluding Load) Front / Rear	lbs (kg)	4495.22 (2039)	4384.99 (1969)	4455.54 (2021)	
TIRES, CHASSIS	1.16	1 Tire Type, P = Pneumatic, SE = Superelastic, C = Cushion		SE	C	C
	1.17	Tire Size, Front		20x50-10	18 x 9 x 12.12	18 x 9 x 12.12
	1.18	Tire Size, Rear		14x55-9	15 x 5 x 11.25	15 x 5 x 11.25
DIMENSIONS	1.19	3 Wheels, Number Front / Rear (x= Drive Wheels)		2X2	2X2	2X2
	1.20	Tread, Front	(in mm)	36.18 (919)	34.53 (877)	34.53 (877)
	1.21	Tread, Rear	(in mm)	7.64 (195)	7.05 (179)	7.05 (179)
	1.22	Wheel Width	deg	5 / 6	5 / 6	5 / 6
	1.23	Height, upright lowered	(in mm)	82.87 (2105)	82.87 (2105)	82.87 (2105)
	1.24	Freelift (w/ LBR)	(in mm)	4.33 (110)	4.33 (110)	4.33 (110)
	1.25	Height Over Head Guard Std	(in mm)	86.85 (2206)	86.85 (2206)	86.85 (2206)
	1.26	Height Floor to Battery Bottom Std	(in mm)	3.39 (87)	3.39 (87)	3.39 (87)
	1.27	Seat Height (Floor to Front Corner)	(in mm)	44.09 (1120)	44.09 (1120)	44.09 (1120)
	1.28	Step Height (Floor to Top of Step)	(in mm)	17.83 (453)	17.83 (453)	17.83 (453)
DIMENSIONS	1.29	Floorboard Height (Floor to Center of Floorboard)	(in mm)	28.11 (714)	28.11 (714)	28.11 (714)
	1.30	Hood Height (Floor to Top of Hood)	(in mm)	38.46 (977)	38.46 (977)	38.46 (977)
	1.31	Length to Face of Forks	(in mm)	77.95 (1980)	75.04 (1900)	79.21 (2012)
	1.32	Width (OAW-Across Drive Tires)	(in mm)	44.25 (1124)	43.54 (1106)	43.54 (1106)
	1.33	Width (OAW-Across Drive Fenders)	(in mm)	41.50 (1044)	41.50 (1054)	41.50 (1054)
	1.34	Width (Across Frame)	(in mm)	41.50 (1054)	41.50 (1054)	41.50 (1054)
	1.35	Fork Dimensions	(in mm)	1.5 (38) x 4.0 (102) x 102 (2067)	1.5 (38) x 4.0 (102) x 40 (1067)	1.5 (38) x 4.0 (102) x 40 (1067)
	1.36	Fork Carriage Width	(in mm)	37.0 (940)	37.0 (940)	37.0 (940)
	1.37	Ground Clearance Minimum Unladen (Upright)	(in mm)	2.0 (51)	2.0 (51)	2.0 (51)
	1.38	Ground Clearance Center of Wheelbase	(in mm)	4.09 (104)	4.09 (104)	4.09 (104)
DIMENSIONS	1.39	Right Angle Stack (42x48) + 8 in clear	(in mm)	137.17 (3434)	134.84 (3425)	138.58 (3526)
	1.40	Axle Width for Pallets 1200 x 1200 Crossways (42x42) + 8 in clear	(in mm)	131.30 (3340)	129.21 (3282)	132.91 (3332)
	1.41	Axle Width for Pallets 800 x 1200 Crossways (32x48) +200mm (8 in) clear	(in mm)	135.75 (3448)	130.73 (3359)	137.17 (3484)
	1.42	Turning Radius	(in mm)	63.27 (1607)	60.35 (1549)	64.60 (1645)
	1.43	Travel Speed Unladen / Unladen	mph (kph)	10.0 (16.1) / 10.0 (16.1)	7.58 (12.2) / 7.58 (12.2)	7.71 (12.4) / 7.71 (12.4)
	1.44	Lift Speed Unladen / Unladen (48V)	fpm (rpm)	1.41 (0.43) / 2.07 (0.63)	1.15 (0.35) / 1.84 (0.56)	1.15 (0.35) / 1.84 (0.56)
	1.45	Lowering Speed Unladen / Unladen (48V)	fpm (rpm)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)
	1.46	Lift Speed Unladen / Unladen (36V)	fpm (rpm)	1.15 (0.35) / 1.94 (0.59)	0.98 (0.30) / 1.84 (0.56)	0.98 (0.30) / 1.84 (0.56)
	1.47	Lowering Speed Unladen / Unladen (36V)	fpm (rpm)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)	2.07 (0.63) / 1.90 (0.58)
	1.48	Max Drawbar Pull Unladen / Unladen	lbf (N)	3812.09 (16957) / 2597.89 (11556)	3818.63 (16987) / 2452.89 (10911)	3708.90 (16948) / 2543.04 (11312)
MSC	1.49	Max Groundability Unladen / Unladen	%	28.2 / 27.6	34.8 / 23.4	29.2 / 24.0
	1.50	Service Brake		Electric	Electric	Electric
	1.51	Battery Weight (Min / Max) 1	lbs (kg)	2500.04 (1134) / 3635.42 (1649)	2893.43 (1175) / 2896.87 (1314)	2500.04 (1134) / 3635.42 (1649)
	1.52	- Diameter of Drive Motor	(in mm)	7.87 (200)	7.87 (200)	7.87 (200)
	1.53	- Diameter of Hydraulic Motor	(in mm)	7.87 (200)	7.87 (200)	7.87 (200)
	1.54	- Drive, Steer, Hydraulic Motor Control		AC / Inverter	AC / Inverter	AC / Inverter
	1.55	Sound Level, Drive Ear According to DIN 12053	dBA	67	67	67
	1.56	Towing Coupling, Class / Type DIN		Pn	Pn	Pn